Nom : Spray grease remover 400 ml Page : 1 / 8 Société : VAR

1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING ENTREPRISE

1.1. Product identifier

Product name: Spray grease remover 400 ml

Product code: NL-75300

1.2. Relevant identified uses of the substance or mixture and uses advised against

N/A

1.3. Details of the supplier of the safety data sheet

Name: VAR.

Address: 19 AVENUE GUSTAVE EIFFEL

28630 GELLAINVILLE

FRANCE

Telephone: +33 (0) 2 37 33 37 10 Fax: +33 (0) 2 37 33 37 17 contact@vartools.com http://www.vartools.com

Emergency telephone number: +33 (0)1.45.42.59.59.

Association/Organisation: INRS/ORFILA http://www.centres-antipoison.net



2.1. Classification of the substance or mixture

Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:

Properties / Symbols:

F+ Extremely flammable

Xi Irritant

N Dangerous for the environment

R Phrases:

R12 Extremely flammable.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

EC regulation criteria 1272/2008 (CLP):



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects: No other hazards

2.2. Label elements

Symbols:







Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effe cts.



Date: 03/05/2017

Nom: Spray grease remover 400 ml

Date: 03/05/2017 Page: 2 / 8 Société: VAR

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 ℃/122年.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contents:

dipentene; limonene;

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards: No other hazards

3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>=20% - <30% Distillates (petroleum), hydrotreated light; Kerosine â€" unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presenc

Index number: 649-422-00-2, CAS: 64742-47-8, EC: 265-149-8

Xn; R65



3.10/1 Asp. Tox. 1 H304

>=25% - <30% dipentene; limonene;

Index number: 601-029-00-7, CAS: 5989-27-5, EC: 227-813-5

Xi,N; R10-38-43-50/53



2.6/3 Flam. Liq. 3 H226



3.2/2 Skin Irrit. 2 H315



3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317



Nom: Spray grease remover 400 ml

4.1/A1 Aquatic Acute 1 H400



4.1/C1 Aquatic Chronic 1 H410

>=20% - <25% propane

Index number: 601-003-00-5, CAS: 74-98-6, EC: 200-827-9

Date: 03/05/2017 Page: 3 / 8

Société: VAR

F+; R12

2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

>=10% - <12,5% butane

Index number: 601-004-00-0, CAS: 106-97-8, EC: 203-448-7

F+; R12



2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

>=5% - <7% butane

Index number: 601-004-00-0, CAS: 75-28-5, EC: 200-857-2

F+; R12



2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

>=3% - <5% 1,2-dichloropropane; propylene dichloride Index number: 602-020-00-0, CAS: 78-87-5, EC: 201-152-2

F,Xn; R11-20/22



2.6/2 Flam. Liq. 2 H225



3.1/4/Oral Acute Tox. 4 H302

Nom : Spray grease remover 400 ml

4 - FIRST AID MEASURES

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsedimmediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: None

5 -FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use dust fire extinguisher, CO₂ or foam.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6 – ACIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working

Date: 03/05/2017 Page: 4 / 8

Société: VAR

Date: 03/05/2017 Page: 5 / 8

Société: VAR

Nom: Spray grease remover 400 ml

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

8. EXPOSURE CONTROL/PERSONAL PROTECTION

8.1. Control parameters

Distillates (petroleum), hydrotreated light; Kerosine â€" unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presenc - CAS: 64742-47-8

TLV TWA - mg/m3 200 ,skin A3

TLV STEL - Skin A3

butane - CAS: 106-97-8

ACGIH, 1000 ppm - Notes: CNS impair

butane - CAS: 75-28-5

ACGIH, 1000 ppm - Notes: CNS impair

1,2-dichloropropane; propylene dichloride - CAS: 78-87-5

ACGIH, 10 ppm - Notes: (SEN), A4 - URT irr, body weight eff

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance and colour: Limpid colourless

Odour: Characteristic citrus

pH: N.a.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A. Flash point: <0°C Evaporation rate: N.A. Vapour pressure: N.A.

Relative density: 0,78 gr/ml c.ca Solubility in water: Insoluble

Lipid solubility: Soluble

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.

Date: 03/05/2017 Page: 6 / 8

Nom : Spray grease remover 400 ml Société : VAR

Oxidizing properties: N.A.

9.2 Other information Miscibility: N.A.

Fat Solubility: N.A. Conductivity: N.A.

Substance Groups relevant properties N.A.

10 - STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity:
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity:
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12 - ECOLOGICAL INFORMATION

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

N.A.

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

Date: 03/05/2017 Page: 7/8

Société: VAR

Nom: Cleansing foam for frame and fork

13 – DISPOSAL CONSIDERATION

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14- TRANSPORT INFORMATION

14.1 UN number:

ADR-UN number: 1950 IATA-UN number: 1950 14.2 UN proper shipping name:

ADR-Shipping Name: Aerosol with capacity of 1000 cm3 0r less

14.3 Transport hazard class(es):

ADR-Class: 2

ADR-Label: **UN 1950 Aerosols**

IATA-Class: 2.1 IMO-Class: 2.1 14.4 Packing Group:

15- REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Dir. 2006/8/EC

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 453/2010 (Annex I)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions:

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II): N.A.

15.2. Chemical safety assessment

No

16- OTHER INFORMATION

Text of phrases referred to under heading 3:

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Nom: Cleansing foam for frame and fork

H411 Toxic to aquatic life with long lasting effects.

H336 May cause drowsiness or dizziness.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU. This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

Date: 03/05/2017 Page: 8 / 8 Société: VAR

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

Derived No Effect Level. DNEL:

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. International Nomenclature of Cosmetic Ingredients. INCI:

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

Long-term exposure. LTE:

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

Short-term exposure. STE: Short Term Exposure limit. STEL: STOT: Specific Target Organ Toxicity. Threshold Limiting Value. TLV:

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.

DISCLAIMER LIABILITY: Despite the care of Bring in the drafting of this document No liability can be accepted for damages Case ou accident resulting from the use son. Before USE this product to a request for a new e pour tests, Jun study compatibility DEPTH Materials and A Risk analysis should be Make .The information contained in the present safety data sheet comes from our experience directly. These are good faith All data and corresponding to the present state of our heuristic knowledge about the safety of the products range VAR® to date update indicated at the top of page 1. This paper does not in None of the CAS User Knowing and applying all the texts regulating son activity. He will be the only responsible precautions Related to the use of Products range VAR®. All regulatory requirements-have mentioned Simply pour aider but the recipient COMPLETE obligations Who obligations of UN LORs use the dangerous or not. This list is not exhaustive Must Be regarded as.